



| | | | |
|--|--------------|--------------|--------------|
| 5 | Clamp | Copper alloy | Sn Plated |
| 4 | Cage | Copper alloy | M3/Ni Plated |
| 3 | Screw | Steel | M3/Zn Plated |
| 2 | Cover | PA66 | UL94V-0 |
| 1 | Housing | PA66 | UL94V-0 |
| ITEM | NAME OF PART | MATERIAL | NOTES |
| UL 标准 / UL Standard: B C D | | | |
| 额定电压/电流 / Rated Voltage(V)/Current(A) 300/15 / 300/10 | | | |
| IEC 标准 / IEC Standard: / / | | | |
| 过压类别 / Overvoltage Category / 污染等级 / Pollution Degree III/2 | | | |
| 额定电压/电流 / Rated Voltage(V)/Current(A) 400/20 | | | |
| 额定脉冲电压 (KV) / Rate Impulse Voltage (KV) 4 | | | |
| 额定扭矩 / Torque - Tightening (N·m/Lb.in) M3 0.5/4.43 | | | |
| 导线范围 (硬线和软线) / Wire Range (rigid and flexible) (mm ² / AWG) 1.0~2.5 / 28~12 | | | |
| 间距 / Pitch (mm) / 线数范围 / Poles 7.5 / N=02~16P | | | |
| 导线长度 / Stripping length (mm) 7-8 | | | |
| 使用温度范围 / Operating temperature (°C) -40~+105 | | | |
| 符合RoHS环保要求 / Conform to RoHS Yes | | | |
| 标准颜色编号 / Standard color number: / | | | |
| PANTONE / RAL / | | | |

MATERIAL: SURFACE:

MAT NO.:
STATUS:
APPD:
CHKD:
DRT:

NAME: **宁波三安电子科技有限公司**
Sanan Electrical Technology Co. Ltd

DRAWING NO.: **ZESAK-7.5-XXP-1Y-1000A(H)**
TYPE: SCALE: SHEET 1/1

| | | | | | | | | | | | | | | |
|------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| 公差 (General tolerances) (mm) | 0 | >3 | >6 | >10 | >18 | >30 | >50 | >80 | >120 | >180 | >250 | >315 | >400 | >500 |
| | ±0.12 | ±0.18 | ±0.22 | ±0.26 | ±0.31 | ±0.37 | ±0.57 | ±0.80 | ±1.05 | ±1.15 | ±1.60 | ±2.20 | ±2.50 | |

0.1/10
±Z